



Ultrasonic Transducer Generators



#90-4200
#90-4210



APC International's Advanced Ultrasonic Generators offer a full range of features to meet any precision cleaning requirements. These generators will deliver precise cleaning, quickly, consistently, and cost effectively.

FEATURES:

- Bright digital display
- Status indicators on safety and fault alarms
- Protection from short-circuit and overload
- User-adjustable power controls
- Compact size aluminum cabinet

TECHNICAL SPECIFICATIONS

Item #	90-4200	90-4210
Input Voltage	120V or 220V 50/60 Hz	220V or 240V 50/60 Hz
Output Power	300 Watts	600, 900, 1,200 Watts
Output Frequency*	28 or 40 kHz	28 or 40 kHz
Dimensions	210 x 390 x 140 mm	210 x 360 x 190 mm
Weight	6 kgs.	19 kgs.

When Requesting a Quote or Placing an Order:

Specify the model number, output frequency, output power, and input voltage.

Keep in mind the Ultrasonic generators are set up for 6 transducers per 300 Watts of power thus:

- 300W generator requires 6 sandwich transducers
- 600W generator requires 12 sandwich transducers
- 900W generator requires 18 sandwich transducers
- 1,200W generator requires 24 sandwich transducers

*Contact an APC Representative for generators with output figures above 40kHz.



Rev. 5/12/14